

# AQF150E Series

150 W AC/DC Switching Power Supply – Enclosed

CoolPower  
Solutions

- Enclosed Switching Power Supply
- PFC Function
- 3.3 VDC to 48 VDC Single Output
- 3000 VAC Input to Output Isolation
- 150Watt with 18CFM FAN
- Ultra Compact Size: 5.0 x 3.24 x 1.5 Inches
- 2-Years Product Warranty



## Electrical specifications


Model No.	AQF150E-3.3S	AQF150E-5S	AQF150E-12S	AQF15E-15S	AQF150E-24S	AQF150E-48S		
Max Output Wattage - Convection (W)	52W	80W	95W	95W	95W	95W		
Max Output Wattage – 18CFM Fan (W)	82.5W	125W	125W	125W	125W	125W		
Input	Voltage						90-264 VAC or 120-370 VDC	
	Frequency (Hz)						47-63 Hz	
	Current (Full load)						3 A max. (115 VAC) / 1.5 A max. (230 VAC)	
	Inrush Current (<2ms)						30 A max. (115 VAC) / 60 A max. (230 VAC)	
	Leakage Current						3.5 mA max.	
	Power Factor						PF>0.97 (115 VAC) / PF>0.93 (230 VAC) at Full Load	
Output	Voltage (V.DC.)		3.3V	5V	12V	15V	24V	48V
	Voltage Accuracy		±2%					
	Current Conv (A) max		16	16	7.9	6.33	3.95	1.98
	Current 18CFM (A)max		25	25	10.4	8.33	5.2	2.6
	Line Regulation		±1% (LL-HL) (typ.)					
	Load Regulation		±1% (5-100%) (typ.)					
	Minimum Load		0%					
	Max Capacitive Load		470-23,000µF depending on model					
	Ripple & Noise (Vp-p)		100 mV max	100 mV max.	1% max	1% max	1% max	1% max
	Efficiency		68%	70%	75%	75%	75%	75%
	Hold-up Time		18 ms min.					
	Switching Frequency		67 kHz					
Protection	Over Power Protection		Auto recovery					
	Over Voltage Protectio		Auto recovery					
	Short Circuit Protection		Auto recovery					
Isolation	Input-Output (V.AC)		3000V					
	Input-FG (V.AC)		1500V					
	Output-FG (V.AC)		500V					
Environment	Operating Temperature		-25°C...+70°C (with derating)					
	Storage Temperature		-40°C...+85°C					
	Temperature Coefficient		±0.02%/°C					
	Humidity		95% RH					
	MTBF		>100,000 h @ 25°C (MIL-HDBK-217F)					
	Vibration		10~500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes.					
Physical	Dimension (L x W x H)		5.0 x 3.24 x 1.5 Inches ( 127.0 x 82.2 x 38.1 mm ) Tolerance ±0.5 mm					
	Weight		470 g					
	Cooling Method		Free air convection / 18CFM Forced Air					
Safety	Agency Approvals		CE, UL					
EMC	EMI		EN 55022 class B (Conducted & Radiated Emission)					
	EMS (Noise Immunity)		EN 55024					

# AQF150E Series

150 W AC/DC Switching Power Supply – Enclosed

CoolPower  
Solutions



## Mechanical Specifications (top view)



Pin no:	Single
1	AC IN (L)
2	AC IN (N)
3	FG
4	+DC OUT
5	+DC OUT
6	-DC OUT
7	-DC OUT

CoolPower  
Solutions

## DERATING



## BLOCK DIAGRAM

