


Mascot 8314

100mA Chargers for NiCD/NiMH Batteries

CoolPower
Solutions

- Konstantstrømlader for NiMH/NiCd-batterier
- For 50 mAh-1 Ah batterier
- Lineær
- Termosikring i transformator, polvendings- og kortslutningssikker
- Plugg-inn enhet
- Lysdiode indikerer lading

- Constant current charger for NiMH/NiCd batteries
- For 50 mAh-1 Ah batteries
- Linear
- Thermal fuse in transformer, protected against reversed polarity and short circuit proof
- Plug-in unit
- LED indicates charging



Tekniske data

Inngangsspenning:
Ladespenning
(1-12 celler samtidig):
Ladestrøm - konstant:
Temperaturområde:
Strømbegrensning:
Isolasjonsklasse:
Elektrisk sikkerhetsstandard:
EMC standarder

- Emisjon:
- Immunitet:

Utgangsterminaler

- Sek. ledning med/uten plugg:

Mål uten plugg (LxBxH):
Vekt:

Technical specifications

Input voltage: 230 VAC +6/-10%, 50/60Hz
Charging voltage
(1-12 cells simultaneously): Max. 30 V
Charge current - constant: 60 mA
Temperature range: -10°C - +40°C
Current limiting: Ja / Yes
Insulation class: II
Electrical safety standard: EN 60065, EN 60950
EMC standards

- Emission: EN 50081-1
- Immunity: EN 50082-1

Output terminals

- Cord with/without plug: Tilbehør / Accessories

Dimensions without plug (LxWxH): 75 x 47 x 49 mm
Weight: 220 g

Versjoner Versions	14 t lading - batterikapasitet 14 h charging - battery capacity
5 mA	50 mAh
10 mA	100 mAh
15 mA	150 mAh
25 mA	250 mAh
30 mA	300 mAh
35 mA	350 mAh
45 mA	450 mAh
50 mA	500 mAh
60 mA	600 mAh
80 mA	800 mAh
90 mA	900 mAh
100 mA	1 Ah