


Mascot 8714CC

400mA Chargers for NiCD/NiMH Batteries

CoolPower
Solutions

- Konstantstrømlader for 1-10 NiMH/NiCd-celler
- For 500 mAh-4 Ah batterier (C/10 lading)
- Lineær
- Termosikring i transformator, termisk beskyttelse i regulator, polvendings- og kortslutningssikker
- Plugg-inn enhet
- Lysdiode indikerer lading
- Kan leveres med medisinsk godkjenning (EN 60601) på forespørsel

- Constant current charger for 1-10 NiMH/NiCd cells
- For 500 mAh-4 Ah batteries (C/10 charging current)
- Linear
- Thermal fuse in transformer, thermal protection in regulator, protected against reversed polarity and short circuit proof
- Plug-in unit
- LED indicates charging
- Available with medical approved (EN 60601) upon request



Tekniske data

Inngangsspenning:

Ladespenning

- Ved tomgang:
- Ved 400 mA:

Ladestrøm

- Innstillbar:
- < 8,4 V må justeres til:

Strømtrekk fra batteri

ved frakoblet nett:

Temperaturområde:

Isolasjonsklasse:

Elektrisk sikkerhetsstandard:

EMC standarder

- Emisjon:
- Immunitet:

Utgangsterminaler

- Sek. ledning med/uten plugg:

Mål uten plugg (LxBxH):

Vekt:

* Kan på bestilling leveres med andre ladestruer.

* Can on request be delivered with other charge current.

Technical specifications

Input voltage:

230 VAC +6/-10%, 50/60Hz

Charging voltage

- At no load: Max. 24 V
- At 400 mA: Min. 12 V

Charge current

- Adjustable: 50-400 mA
- < 8,4 V must be limited to: 250 mA

Leakage current from battery
when mains switched off:

< 0,1 mA

Temperature range:

-20°C - +30°C

Insulation class:

II

Electrical safety standard:

EN 60065, EN 60950

EMC standards

- Emission: EN 50081-1
- Immunity: EN 50082-1

Output terminals

- Cord with/without plug: Tilbehør / Accessories

Dimensions without plug (LxWxH):

100 x 51 x 63 mm

Weight:

450 g