



- AC fans with internal rotor shaded-pole motor. Impedance protected against overloading.
- Metal fan housing, impeller of mineral-reinforced plastic PA.
- Air exhaust over struts. Rotational di-

rection CCW looking at rotor.

- Electrical connection via 2 flat pins 2.8 x 0.5 mm.
- Fan housing with ground lug for screw M4.
- Mass 325 g.

SERIES 9900

119x119x25mm

Air Flow		Nominal Voltage	Frequency	Noise		Sinter-Sleeve Bearings		Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀		Curve	Type
m ³ /h	CFM			V	Hz	dB(A)	bels				○ ●	Watt		
84	49.4	230	50	29.5	4.4	●	9.5	1850	-40...+80	57 500 / 22 500		1	9956L	
104	61.2	230	50	35.5	4.7	●	10	2250	-40...+80	57 500 / 22 500		2	9956M	
117	68.9	230	50	37	5.0	○	14	2450	-20...+70	47 500 / 22 500		3	9950	
117	68.9	230	50	37	5.0	●	14	2450	-40...+70	47 500 / 22 500		3	9956	
100	58.9	115	60	34.5	4.6	●	8	2100	-40...+80	62 500 / 25 000		4	9906L	
111	65.3	115	60	37	5.0	●	8	2450	-40...+80	62 500 / 25 000		5	9906M	
135	79.5	115	60	42	5.4	○	12	2850	-20...+70	52 500 / 25 000		6	9900	
135	79.5	115	60	42	5.4	●	12	2850	-40...+70	52 500 / 25 000		6	9906	

