

- Output sockets with blackout protection
- Reduced weight and dimensions
- Low Noisiness
- Easy installation
- Use with Personal Computer, Modem, Workstation or NAS Server



Specifications

Model	ECO0K50	ECO0K70	ECO0K90	ECO1K1	ECO1K3
Nominal power (VA)	500	700	900	1100	1300
Nominal active power (W)	300	420	540	660	780
Power factor	0.6				
Technology	Easy interactive				
Nominal input voltage	Single phase 230 Vac				
Input voltage range	± 20 %				
Nominal input frequency	50 / 60 Hz (automatic selection)				
Input frequency range	± 5 %				
Nominal output voltage	Single phase 230 Vac				
Output voltage regulation (Line mode)	As Input				
Output voltage regulation (Battery mode)	± 5 %				
Output frequency	50 / 60 Hz (automatic selection)				
Output Inverter waveform	Modified Sinewave				
Overload capability	< 130 %				
Transfer time	2-4 ms typical				
Backup time	5 min at 100% load - 10 min typical				
Nominal battery voltage	12 Vdc				
Batteries: Sealed maintenance free Lead Acid	1 internal 12 V 4,5 Ah	1 internal 12 V 5 Ah	1 internal 12 V 7,2 Ah	1 internal 12 V 7,2 Ah	1 internal 12 V 9 Ah
Recharge time (typical)	4 hours				
Audible noise	< 40 dBA at 1 m				
Cooling	Natural				
Weight	2,5 kg	2,6 kg	3,5 kg	3,6 kg	4,0 kg
Dimensions (WxHxD)	207 x 120 x 228 mm				
Operating Temperature Range	0-40 °C (20-25 °C recommended for longer battery life time)				
Relative Humidity Range	<95% (non-condensing)				
Maximum Altitude	3000 m				
Protection Level	IP20				
Outlets	2 UPS outputs, IEC320 – C13 type				
Equipped with	2 output cables IEC type				
Certifications	CE (standards: Low voltage Directive IEC EN 62040-1; EMC Directive IEC EN 62040-2, classification IEC EN 62040-3				
Warranty	2 years				