

ERA-Strip Series

600 – 800 VA Line-Interactive UPS with Schuko outputs

CoolPower
Solutions

- Easy Interactive Technology
- Hot Swap Battery
- Low Noise
- Easy to install
- Use with Personal Computer, Inkjet, Modem, Workstation or LAN Server



Specifications

Model	FGCERAST0K6	FGCERAST0K8
Max Output Power (VA)	600	800
Recommended for	Computer (W)	400
	Monitor	LCD
	Printer	Laser / Inkjet
Nominal Input Voltage (Vac)	220 / 230	
Technology	Easy Interactive	
Input Voltage Range (%)	±20	
Input / Output Frequency (Hz)	50 / 60 (automatic selection)	
Input Frequency Range (%)	± 5	
Nominal Output Voltage (Vac)	220 / 230	
Output Voltage Regulation (Line mode)	As Input	
Output Voltage Regulation (Battery mode) (%)	± 5	
Output Inverter Waveform	Modified Sinewave	
Overload Accepted	< 130 %	
Certifications	CE (standards: Low voltage Directive IEC EN62040-1-1; EMC Directive IEC 62040-2 / EN 50091-2)	
Backup Time (min)	5 min at 100% load - 10 min typical	
Nominal Battery Voltage (Vdc)	12	
Batteries: Sealed maintenance free Lead Acid	1 unit 12 V 4,5 Ah	1 unit 12 V 5,0 Ah
Recharge Time (Typical)	8 hours	
Hot Swap Battery	Included	
Audible Noise (at 1m) (dBA)	< 40	
Cooling	Natural	
Weight (kg)	3,2	3,5
Dimensions (WxHxD mm)	124 x 166 x 202	
Environmental Specifications	Temperature 0-40 °C Humidity 0-95% without condensation Maximum altitude 3000mt	
Interfaces	RS232 and USB ports included	
Telephone and modem protection	RJ11 / RJ45	
Software	Included WinPower software downloadable free of charge	
Outlets	4 UPS outputs, Schuko type + 2 filtered outputs, Schuko type	
Equipped with	AC input cable	
Warranty	2 years	