

# Power Server Series

1500-2200 VA Line Interactive UPS

CoolPower  
Solutions

- Line Interactive technology
- Stabilization through AVR
- True Siniwave
- Tower or Rack mounting
- Hot Swap Battery
- SNMP adapter included
- RS-232 and USB Interfaces
- UPS Management Software
- LAN Protection (RJ45) and Phone Protection (RJ11)
- Full cables and accessories equipment



Power Server Model	Power Server 3000	Power Server 4500
Recommended for:	1 LAN Server + 4 Clients	1 LAN Server + 7 Clients
Power (cosφ 0,7)	1500 VA	2200 VA
Technology	Line Interactive with AVR	
Nominal Inout Voltage	220/230 V	
Input Voltage Range	+20% - 25%	
Input/Output Frequency	50/60 Hz (automatic selection)	
Input Frequency Range	+ -5%	
Nominal Output Voltage	220/230 V	
Output Voltage Regulation (Line Mode)	by AVR (Automatic Voltage Regulation)	
Output Voltage Regulation (Backup Mode)	+ -5%	
Output Inverter Waveform	True Siniwave	
Overload Accepted	< 130%	
Transfer Time (Typical)	0 ms	
Bypass	No	
Harmonic Distorsion (THD)	< 3 %	
Certifications	CE - UL	
Batteries Nominal Voltage	48 Vcc	
Batteries Type	Sealed lead acid battery, free maintenance	
Batteries Characteristics	4 x 12V 7Ah	4 x 12V 9Ah
Batteries Typical Recharge Time (hours)	8	
Back Up Time (Typical)	10-15 minutes	
Audible Noise (At 1 Metre)	< 45 dBA	
Cooling	Fan cooling	
Weight (kg)	27	32
Dimensions (WxHxD) cm	42x9x38	
Environmental Specifications	Temperature: 0-40 °C - Humidity: 0-95% (without condensation) - Altitude: max 3.000 m	
SNMP adapter for Ethernet LAN	Included	
Rs 232 Interface	2 x RS-232 ports + USB adapter	
Filtered Telephone Plug	RJ45/RJ11 Included	
Ups Software	Software included	
	Compatible with Win 95/98/ME/NT/2000, XP	
Number of Output Sockets	3 x (IEC Type) + 3 x Suko	
Equipped with:	AC input cable, 2 output cables, 2 serial cables, 1 USB-RS232 adapter, 1 phone cable 1 adapter SNMP for Ethernet LAN, mounting brackets for 19" rack, 2 tower stands, Software	